



- High quality diffuser with inside lens ensures high uniformity
- Up to 110lm/W
- Strong frame with extrusion aluminum
- IP20 (IP40 for front lighting panel)
- 50,000hrs lumen maintenance - L70@25 °C
- 2ftx2ft, 4ftx1ft, 4ftx2ft

## Light is uniformity

# LEDCOMFO® Louver V3

## General Edition

Introducing our latest LED backlit louver solution designed specifically for indoor applications.



TRAXON | ecue  
MEMBER OF PROSPERITY GROUP

OSRAM



## LED COMFO® Louver V3 (General Edition)




LED COMFO® Louver V3 is the latest LED back-lit louver solution for office applications. The newly product design provides high uniformity based on 2ft×2ft, 4ft×1ft, 4ft×2ft size, which available for four kinds of installation including recessed, suspended, PCV, integrated ceiling, fulfilling the different requirements of customers.

### Applications

- Offices
- Metros
- Hospitals
- Public buildings

### Photometrics



### Advantages & Benefits

#### Comfortable with high uniformity

- High quality diffuser with inside lens ensures high uniformity
- Without flicker
- Up to 110lm/W

#### Stable performance with safety and reliability

- 1.2KV line to line surge protection
- PF 0.95
- Strong frame with extrusion aluminum
- IP20 (IP40 for front lighting panel)
- 50,000hrs lumen maintenance - L70@25°C

#### Full range to fulfill all applications

- 2ft×2ft, 4ft×1ft, 4ft×2ft
- Recessed, suspended, integrated ceiling, PCV
- 3000K, 4000K, 6500K

### Dimensions

#### Recessed/Suspended/PCV Mounting

	L	L	L
	W	W	W
	H	H	H
	2ft×2ft	4ft×1ft	4ft×2ft
L	595mm	1195mm	1195mm
W	595mm	295mm	595mm
H	25mm	35mm	35mm

#### Integrated Ceiling Mounting

	L	L	L
	W	W	W
	H	H	H
	2ft×2ft	4ft×1ft	4ft×2ft
L	600mm	1200mm	1200mm
W	600mm	300mm	600mm
H	25mm	35mm	35mm

### Product Configurator

#### LCM LV V3

#### Dimension

#### Power

#### CRI - CCT

#### Mounting

#### Packing Quantity

Dimension	Power	CRI - CCT	Mounting	Packing Quantity
0606 2ft×2ft	34W 34W - 3740lm@4000K - 2ft×2ft, 4ft×1ft	830 Ra80, 3000K	(blank) Recessed/Suspended/PCV	VS8 8pcs - 2ft×2ft
0312 4ft×1ft	60W 60W - 6600lm@4000K - 4ft×2ft	840 Ra80, 4000K	IT Integrated ceiling	VS5 5pcs - 4ft×1ft
0612 4ft×2ft	80W 80W - 8800lm@4000K - 4ft×2ft	865 Ra80, 6500K		VS4 4pcs - 4ft×2ft

Control	Voltage	Frequency	Beam angle
ON/OFF	220-240V AC	50/60 Hz	110°

v1.0 08/23 · Technical data subject to variation and change without notice.

©2023 Traxon Technologies. All rights reserved. Errors and omission excepted. All images used are for illustrative purposes only and not intended to reflect actual product performance. Official authorized licensee of the OSRAM trademark.

Traxon e:cue

Sales enquiry: info@traxon-ecue.com  
www.traxon-ecue.com