

Butler PRO e:pix



Butler PRO e:pix

The e:cue Butler PRO e:pix is an e:net to e:pix interface for the e:cue Lighting Application Suite (LAS). It controls up to 16 e:pix universes with 2,048 channels per universe. Connection to the server runs via Ethernet interface with 100 MBit/s. All cabling, Ethernet and e:pix, uses CAT5 RJ45 connections. Using a LC display with 2 lines by 20 characters, all basic configurations can be done with the set of four cursor keys and an OK key. When online, the LC display shows status messages from the Butler PRO e:pix. The Butler PRO e:pix is the optimal interface for running huge numbers of e:pix universes. The system is installed in standard 19-inch racks.

Main features

- Controls up to 32,768 e:pix channels in 16 e:pix universes
- Basic configuration via LC display and cursor keys
- Display of status messages while operating
- 100 MBit system interconnect for e:net over Ethernet

Delivery scope

Item code

- | | |
|---------------------------|-------------|
| • Butler PRO e:pix | AA628610035 |
| • Rack mounting brackets | |
| • Power chords DE, US, UK | |
| • Welcome note | |

e:cue Interfaces

Lighting applications are heterogenous by nature. e:cue interfaces serve to integrate many networks, protocols and third party products into e:cue solutions. They also aid in applying special control functions for fixtures, they integrate analog or mechanical signaling into the digital world and offer bridging functions. e:cue interfaces are the links to bring together the many techniques and technologies of lighting control.

Product specifications

Dimensions (W x H x D)	482 x 44 x 142 mm / 19 x 1.7 x 5.6 in (incl. mounting brackets)
Weight	1.2 kg / 2.65 lbs
Power supply input	100 ... 240 V AC, 50/60 Hz
Power consumption	max. 20 W
Operating temperature	0 ... 40 °C / 32 ... 104 °F
Storage temperature	-20 ... 70 °C / -4 ... 158 °F
Op. / storage humidity	0 ... 80% RH, non-condensing
Protection class	IP20
Housing	Steel, front powder coated
Mounting	in 19-inch standard racks
Certificates	CE, ETL, UKCA

Interface specifications

Outputs	16 e:pix ports galvanically isolated (2 ports/isle) for 1 kV RJ45 receptacle connector Traxon pin configuration
System link	1 x e:net (RJ45)
User interfaces	4 + 1 cursor keys, LC display
Display	2 x 20 characters LCD display



Intertek

40063765

Conforms to ANSI/UL Std. 60950-1

Certified to CSA Std. C22.2 NO. 60950-1

Dimensions (in mm)

All dimensions in mm

