



Company: _____

Project: _____

Media Pixel Ribbon White Flat Outdoor



The Traxon Media Pixel Ribbon Flat Outdoor is an IP67 flexible strip which can be controlled directly using DMX512. The Flat type Ribbon provides flexibility to fit on any curved surface to accommodate architectural structures. Featuring a 0.66" / 16.7 mm LED pitch with a 3.9" / 100 mm pixel pitch, the Media Pixel Ribbon is available in an assortment of colors and CCT options, has multiple mounting options to meet project needs, and is able to be customized for number of pixels and ribbon lengths.



Product Specifications

Models	W 6500K	W 4000K	W 3000K	W 2700K
Light Source	High intensity SMT White LEDs			
Pixels	61 pixels per roll 3 pixels per ft / 10 pixels per m ¹			
LED pitch	0.66" / 16.7 mm			
Pixel Pitch	3.9" / 100 mm			
Cutting Pitch	3.9" / 100 mm			
CRI for White LED	> 80			
SDCM for White LED	3-steps			
Luminous Flux	281 lm per ft 920 lm per m	281 lm per ft 920 lm per m	266 lm per ft 870 lm per m	260 lm per ft 850 lm per m
Efficacy	92 lm/W	92 lm/W	87 lm/W	85 lm/W
Beam Angle	120°			
Housing	UV resistant clear silicone			
Dimensions (W x H)	0.56" x 0.2" / 14.2 mm x 5 mm			
Max. length	20' / 6.1m per roll			
Weight (per roll)	1.48 lb / 671 g			
Mounting	3M adhesive tape on Ribbon, various mounting channels or mounting clips			
Min. Bend Radius	5.9" / 150 mm			
Regulatory Listing & Safety Approval	cETLus, FCC, RoHS, REACH			
Operating Temperature	-4°F to 122°F / -20°C to +50°C			
Storage Temperature	-40°F to 158°F / -40°C to +70°C			
Environment	IP67 Outdoor Rated; suitable for coastal environments			
Humidity	0 to 90% non-condensing			

Electrical Specifications

Input Voltage	24V DC
Power Consumption (Typ.)	2.9 W per foot / 9.6 W per meter

System Specifications

Control	DMX512
Power Supply	100W 24V DC Outdoor
Addressing Options	Addressing with 3rd party addressing device

1. Pixel per meter can be customized to 5 pixels, 2 pixels or 1 pixel.

Please consult regional sales office for more information, pricing and lead time.

LED CHARACTERISTICS Because LEDs are semiconductor devices, their performances are subject to inherent variability commonly found in semiconductor industry. To improve consistency in performance across the same product, LED manufacturers "sort" LEDs into bins according to different preset parameters, such as forward driving voltage, illumination, etc. Whereas binning is a sorting function, it is not a correction process. Inherent variability in the manufacturing process results always in different binning distributions according to different production lots. Traxon uses automatically binned LEDs on its products, thereby minimizing output variations within the model range.


As with all electronic devices, LED output degrades over time – a term called lumen depreciation. This also explains why it is nearly impossible to expect photometric performances of two LED products with different service life spans to be the same. The rate of LED degrade is a complicate function of many factors such as operating efficiency, duration of continuous operation, and more significantly, environmental conditions (ambient temperature for example). If allowed working under optimal operating temperature range and with good ventilation, LED devices enjoy long service lives over conventional light sources. When using/installing LED devices, care should be taken to ensure that the devices will operate within the operating conditions specified in respective product literature.

Lumen measurement complies with LM-79-08 standard.
Lumen maintenance is calculated based on LM-80 compliant measurement.

Source Specifications

LED Source High intensity SMT White LEDs


Candela Distribution



Light Output

Color	Luminous Flux per ft (lm)	Center Intensity (cd)	Efficacy (lm/W)
White			
2700K	260	286	85
3000K	266	292	87
4000K	281	309	92
6500K	281	309	92

Illuminance at a Distance



For feet multiply by 3.28


■ Horiz.Spread: 114.0°
For fc divide by 10.7

IES and LDT files are available for download from the Traxon website.

Media Pixel Ribbon White Flat Outdoor

Dimensions

Media Pixel Ribbon



Model	Max. Ribbon length with single power feed	Actual product length with endcap at 2-ends, L
DW & W	20' / 6.1m	20'+0.8" / 6.1m+20mm


Remark: For other customized lengths (in multiples of 4" / 100 mm), the actual product length would be customized length + 0.8" / + 20mm.

Connection Accessories

RB CONNECTOR ENDCAP 120OHMP67 (AM400870055)




RB 5PIN STARTER CABLE 1M IP67 (AM400840055)
RB 5PIN STARTER CABLE 3M IP67 (AM400850055)




Wire#	Description	Color
1	Address(P)	Green
2	V-	Black
3	DMX+	Yellow
4	V+	Red
5	DMX-	Blue

RB RJ45 STARTER Y-CABLE IP67 (AM401000055)




RB 5PIN POWER INJ Y-CABLE IP67 (AM400990055)




Mounting Accessories

Silicone mounting clip
MOUNTING CLIP FLAT RB (AM412900055)



Aluminium mounting channels




	U-Channel 1605	U-Channel 1608	U-Channel 2007	V-Channel 3030R
Item Code	AM412910055	AM412920055	AM412930055	AM412940055
W (mm)	0.71"	0.76"	0.93"	1.2"
A (mm)	0.63"	0.65"	0.8"	0.8"
H (mm)	0.51"	0.46"	0.81"	1.8"
Length (mm)	37.4"	37.4"	39"	39"
Material	Aluminium channel, PC cover, 304 stainless steel mounting clips (x 3pcs per length)			

NOTE: Media Pixel Ribbon Flat is mounted to the channel with 3M tape.


Typical Wiring with 5-pin Starter Cable

NOTE: Mounting accessories not shown.



Typical Power Injection with Wiring Y-Cable

NOTE: Mounting accessories not shown.



Power injection is required when ribbon connection length reaches the maximum length with single power feed.

Media Pixel Ribbon White Flat Outdoor

Ordering

Fixtures

Model No.	Description	Item Code
RB.UO.6100300	PX RB CLEAR 827 61PPR 20FT DX F1 IP67 ETL (END CABLE FEED)	AM433370055
RB.UO.6120300	PX RB CLEAR 830 61PPR 20FT DX F1 IP67 ETL (END CABLE FEED)	AM433380055
RB.UO.6130300	PX RB CLEAR 840 61PPR 20FT DX F1 IP67 ETL (END CABLE FEED)	AM433390055
RB.UO.6110300	PX RB CLEAR 865 61PPR 20FT DX F1 IP67 ETL (END CABLE FEED)	AM433400055

TX Connect

Model No.	Description	Item Code
RB.MA.5220000	RB 5PIN STARTER CABLE 1M IP67	AM400840055
RB.MA.5230000	RB 5PIN STARTER CABLE 3M IP67	AM400850055
RB.MA.5270000	RB 5PIN STARTER CABLE 5M IP67	AM415500055
RB.MA.5260000	RB 5PIN POWER INJ Y-CABLE IP67	AM400990055
RB.MA.5240000	RB RJ45 STARTER Y-CABLE IP67	AM401000055
N/A	RB CONNECTOR ENDCAP IP67	AM400860055
RB.MA.5203000	RB CONNECTOR ENDCAP 120OHM IP67	AM400870055

TX Cutting tools

Model No.	Description	Item Code
N/A	PX RIBBON CUTTING TOOL	AM412950055
N/A	PX RIBBON SEALING GLUE 100ML	AM412960055
N/A	RX RIBBON FLAT FIELD CUT ENDCAP 20PC	AM412990055

TX Mounting

Model No.	Description	Item Code
N/A	MOUNTING CLIP FLAT RB 20PC	AM412900055
N/A	U-CHANNEL OUTDOOR FLAT 1605 950	AM412910055
N/A	U-CHANNEL OUTDOOR FLAT 1608 950	AM412920055
N/A	U-CHANNEL OUTDOOR FLAT 2007 1M	AM412930055
N/A	V-CHANNEL OUTDOOR FLAT 3030R 1M	AM412940055

TX Power Supply

Model No.	Description	Item Code
N/A	LED ENGINE 100W 24V OUTDOOR	AM175860055

Addressing Device

Please contact your sales representative for details.